

1296-22, Nakaya, Nishifukai, Nagareyama-shi, Chiba 270-0107 JAPAN

TEL +81-4-7186-6797 FAX +81-4-7186-6798

winches@maxpull.co.jp

Model selection sheet

If there is no product model suitable for your use in the product lineup or you cannot decide on any model, please fill in the required information below and send it to MAXPULL by e-mail or FAX. We will select and recommend the model that is suitable for your use.

♦Customer information						
•Your company's name:	Name of person in charge:					
Department:		l .				
•Address and Zip code:						
•TEL:	•FAX:			•E-mail	:	
Detailed specification	ons		I			
(1)Drive system Man	ual / Electi	<u>ric (</u>	2) Num	nber of u	ınits	units
♦For an electric winch ①Supplied power	AC V	Hz :	Single-	-phase /	Three−p	<u>hase</u>
②Winding speed m/mi	in (If there is	a range o	of spec	ed	m/min~	m/min)
3Operation method	Control panel	/ P	ush bu	tton swi	<u>tch</u>	
◆Specifications common to Electric / Manual Winch ①Tensile force of wire kgf/piece ②Number of wires pieces ③Winding length m ④Groove of wire on drum With / Without						
5Diameter of used wire ϕ						
9 Installation location Out					,	<u></u>
(Salt damage, Waterfront, Dust,			peratur	e, Clean r	oom, Chem	icals, etc.)
1 0Attachment direction Ho		_		ency of		
12Other special notes:						